







# GAM835



## Mixed Service All Position Tire – Chip/Cut Resistant Compound

Features	Benefits
 <p>Optimized tread width ratio</p>	Uniform block stiffness delivers even wear and long mileage
 <p>Three zigzag grooves with Y-style design</p>	Increased traction with reduced stone retention
 <p>Shoulder stepped groove design</p>	Improved protection of casing, increased stability and comfort for the driver
 <p>Deep tread design with cut and chip resistant compound</p>	Superb resistance to tread tearing, impacts and casing damage in on/off road conditions

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					mm	mm	(kg@kPa)	(kg@kPa)		mm		mm		
11R22.5	100EV1494Q	16	H	148/145 K	210	191	3148@848	2901@848	279	490	1054	24	501	60
315/80R22.5	100EV1182Q	22	M	161/157 J	229	248	4627@903	4123@903	312	500	1077	24	490	71
11R24.5	100EV1623Q	16	H	149/146 K	210	191	3248@827	2998@827	279	516	1105	24	478	65

PR Ply Rating    LR Load Range    LI Load Index    SR Speed Rating    RPM Revolutions Per Mile

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.



COMMERCIAL TRUCK TIRES