



GAM851



Dumper Trailer, All Position



Dumper, All Position



Cement Mixer, All Position



Mixed Service

Mixed Service All Position Tire – Chip/Cut Resistant Compound

Features

Benefits



Deep tread design with cut and chip resistant compound

Superb resistance to tread tearing, impacts and casing damage in on/off road conditions



Bold three groove design

Optimized block ratio to provide even wear and reduced noise levels



Enhanced casing construction

Provides improved footprint for excellent handling



3PMSF certified performance

Enhanced traction in mud and snow

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					mm	mm	(kg@kPa)	(kg@kPa)						
385/65R22.5	100EV1749Q	18	J	160 K (158 L)	298	311	4500@903	—	389	495	1072	21	492	77
385/65R22.5	100EV2130Q	20	J	160 K (158 L)	298	311	4990@903	—	389	-	1072	21	-	-
425/65R22.5	100EV854Q	20	L	165 K	311	298 330	5171@827	—	422	518	1125	23	469	89
445/65R22.5	100EV841Q	20	L	169 K	330	311 355	5806@903	—	445	528	1151	23	459	97

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.



COMMERCIAL TRUCK TIRES