

Features	Benefits
Special compound with low rolling resistance and low heat generation	Reduced rolling resistance with improved fuel economy
Four zigzag longitudinal groove design	Excellent highway traction and driving stability
Closed shoulder design	Provides excellent high speed performance, longer mileage and minimizes irregular shoulder wear
Optimized block ratio	Uniform block stiffness delivers even wear and long mileage

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth RF	RPM	Weight
					mm	mm	(kg@kPa)	(kg@kPa)	mm	mm	mm	32nds		kg
11R22.5	100EV1780Q	14	G	144/142 L	210	191	2801@724	2649@724	279	490	1054	26	501	62
295/75R22.5	100EV1672Q	14	G	144/141 L	229	210	2801@758	2574@758	297	478	1021	26	517	57
11R24.5	100EV1446Q	14	G	146/143 L	210	191	2998@724	2724@724	279	518	1110	26	475	65
285/75R24.5	100EV1479Q	14	G	144/141 L	210	-	2801@758	2574@758	282	495	1057	26	499	59

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile



Giti manufactures SmartWay Verified Technologies. Learn more at epa.gov/smartway.

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.