



	Features	Benefits
<u>₩</u> M + S	3PMSF certified performance (315/80R22.5 only)	Enhanced traction in mud and snow
	Wide tread pattern with advanced block and sipe design	Provides excellent traction and winter driving performance
ROBUST	Enhanced casing construction	Provides improved footprint for excellent handling
Soud-Shouldery	Optimized pattern and shoulder design	Provides excellent treadwear and driving comfort

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					mm	mm	(kg@kPa)	(kg@kPa)	mm	mm	mm	32nds		kg
11R22.5	100EV1997Q	16	Н	148/145 L	202	191	3,148@848	2,901@848	279	490	1054	27	501	65
315/80R22.5	100EV896Q	18	J	156/150 L (154/150 M)	229	248	4,001@848	3,352@848	312	500	1077	29	490	73
11R24.5	100EV1625Q	16	Н	149/146 L	210	191	3,248@827	2,998@827	279	516	1105	27	478	71

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

