







GDR638



Regional Drive and All Position Light Duty Tire



Features	Benefits
 Solid pattern design with increased block stiffness	Enhanced traction and braking with improved vehicle stability and driver comfort
 Optimized casing and footprint design	Even, consistent wear throughout tire life
 Specialized tread compound	Improved tread wear resistance and handling characteristics
 New, improved bead construction	Improved bead design for easier rim mounting

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					mm	mm	(kg@kPa)	(kg@kPa)						mm
215/75R17.5	100EV1712Q	14	G	126/124 M	152	171	1701@724	1601@724	211	358	767	18	688	29
235/75R17.5	100EV2140Q	16	G	132/130 M	171	191	2000@758	1901@758	234	371	798	19	662	30
225/70R19.5	100EV2110Q	14	G	128/126 L	171	152	1801@758	1701@758	226	378	810	18	651	34
245/70R19.5	100EV757Q	16	H	136/134 M	191	171	2241@827	2121@827	249	389	838	20	630	37

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.



COMMERCIAL TRUCK TIRES