



GSR231 FS







All Position



Regional

SmartWay Verified Regional All Position Tire

Features	Benefits
 <p>Special compound with low heat generation & longer wear</p>	Provides higher tire mileage and improved fuel economy
 <p>Four groove design</p>	Enhanced tread stiffness, reduce in rolling resistance, reliable control and handling
 <p>Multiple sipes on ribs</p>	Optimum traction & braking
 <p>Optimized footprint distribution</p>	Improves footprint performance to prevent irregular wear

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					mm	mm	(kg@kPa)	(kg@kPa)	mm	mm	mm	32nds		kg
11R22.5	100EV1782Q	14	G	144/142 L	210	191	2801@724	2649@724	279	490	1054	21	501	60
11R22.5	100EV1991Q	16	H	148/145 L	210	191	3148@848	2901@848	279	490	1054	21	501	60
11R24.5	COMING SOON	14	G	—	—	—	—	—	—	—	—	—	—	—
11R24.5	COMING SOON	16	H	—	—	—	—	—	—	—	—	—	—	—
295/75R22.5	100EV1674Q	14	G	144/141 L	229	210	2801@758	2574@758	297	472	1013	21	521	56
GT RADIAL GT279: SEE PAGE 40 FOR MORE INFORMATION														
11R22.5	100EV611G	16	H	148/145 M	210	191	3148@827	2901@827	279	490	1054	21	501	57
11R24.5	100EV682G	16	H	149/146 M	210	191	3248@827	2998@827	279	516	1105	19	478	61
285/75R24.5	100EV761G	14	G	144/141 M	210	-	2801@758	2574@758	282	493	1049	19	503	55

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

Giti manufactures SmartWay Verified Technologies. Learn more at epa.gov/smartway.
Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.



COMMERCIAL TRUCK TIRES