



GT867







All Position



Regional



Regional All Position Tire

Features	Benefits
 <p>Extra wide, deep tread pattern with special compound</p>	Improved, longer tire life
 <p>Three W-shaped pattern design</p>	Improved traction performance and anti-wear properties
 <p>Variable angle design</p>	Improved stone ejection and water evacuation
 <p>Enhanced casing construction</p>	Provides improved footprint for excellent handling

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					mm	mm	(kg@kPa)	(kg@kPa)		mm		mm		
11R22.5	100EV1753Q	16	H	148/145 J	210	191	3148@848	2901@848	279	490	1054	24	501	62
275/70R22.5	100EV2210Q	16	H	150/145 J (154/148 E)	210	229	3352@896	2901@896	277	445	958	24	551	57
295/80R22.5	100EV1793Q	18	J	154/150 J	229	210	3751@848	3352@848	297	488	1049	24	503	69

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.



COMMERCIAL TRUCK TIRES