

Regional Trailer and All Position Light Duty Tire

Features	Benefits
New generation pattern with advanced groove design and extra wide shoulder	Provides excellent shoulder area protection and even footprint for consistent wear
New casing construction	Improved casing strength for exceptional durability and retreadability
Specialized tread compound	Improved tread wear resistance and handling characteristics
3PMSF certified performance (4th Qtr. 2019)	Enhanced traction in mud and snow

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					mm	mm	(kg@kPa)	(kg@kPa)	mm	mm	mm	32nds		kg
215/75R17.5	100EV1451Q	16	Н	135/133 J	152	171	2180@862	2059@862	211	358	767	16	688	29
235/75R17.5	100EV2141Q	16	Н	143/141 J (144/144 F)	171	191	2724@862	2574@862	234	371	798	16	662	32
245/70R17.5	100EV871Q	16	Н	143/141 J (146/146 F)	191	171	2724@876	2574@876	249	366	790	16	668	34
385/65R22.5	100EV1740Q	20	L	164K (158L)	298	311	4990@896	_	389	495	1072	20	492	76

PR Ply Rating LR Load Range

LI Load Index

SR Speed Rating

RPM Revolutions Per Mile



